



Criteria	Points Possible	Points Deducted	Comments
General Appearance - Clean or painted	20		
Horizontal Launch Base - Base is minimum of 2 sq. ft. - Length to tire valve stem from verticle launch tube is 4 ft. minimum	30		
Verticle Land Tube - must be minimum of 4 inches, maximum of 12 inches	15		
Fitting - all tight and taped or sealed Safety Gauge - not necessary on friction type Maximum - 100 PSI for lock down types	20		
Member Knowledge (information found on entry card or by interview judging)	15		
TOTAL	100		

Circle Appropriate Ribbon Placing

Purple	Blue	Red	White
(100-90)	(89-80)	(79-70)	(69 & below)

Judge's Initials



Criteria	Points Possible	Points Deducted	Comments
General Appearance - Clean or painted	20		
Horizontal Launch Base - Base is minimum of 2 sq. ft. - Length to tire valve stem from verticle launch tube is 4 ft. minimum	30		
Verticle Land Tube - must be minimum of 4 inches, maximum of 12 inches	15		
Fitting - all tight and taped or sealed Safety Gauge - not necessary on friction type Maximum - 100 PSI for lock down types	20		
Member Knowledge (information found on entry card or by interview judging)	15		
TOTAL	100		

Circle Appropriate Ribbon Placing

Purple	Blue	Red	White
(100-90)	(89-80)	(79-70)	(69 & below)

Judge's Initials